

Device Information

Product Name: HP LaserJet M4345 MFP
Device Name: HP LaserJet M4345 MFP
Model Number: CB426A
Device Serial Number: CNDV84QGBM
Formatter Number: KM60CWW
CPB: 2.089 (0.0)
SCB: CMNPSL 2.9
Bootloader: LDR 02.70
Firmware Datecode: 20071211 48.051.1
DC Controller: 17
Service ID: 18217
PS Wait Time-out: 300 seconds
Engine Cycles: 16173
Maintenance Kit Interval: 225000
Pages Since Last Maintenance: 16163
Document Feeder Kit Interval: 90000
Pages Since Last Doc Feeder Maintenance: 1014

Memory

Total RAM: 256 MB
DWS: 6.00
Automatic resource saving enabled

Event Log

Number of Entries in Use: 22
Maximum Number of Entries: 50
Three Most Recent Entries:

Number	Page Count	Entry
22	16140	99.00.00
21	16140	99.00.00
20	16140	30.01.08

Installed Personalities and Options

PCLXL (20010402)
PCL (20010402)
PDF (20050131)
PS (20010402)
IOF 32(-): thinprint(active) (20070329) 1.0.0.91
DIMM Slot 1: Empty
EIO 1: Empty
EIO 2: HP Scanner Processor Card
Internal Disk: ST940814AS: 37 GB
USB Storage 1: Ober: 61 MB
Internal Fax
LDAP Gateway: 0.0.0.0
SMTP Gateway: 0.0.0.0
HP MFP Digital Sending Server: 0.0.0.0
Digital Send Advanced

Security

Control Panel Lock: None
Control Panel Password: Disabled
Write Protect: Disabled
File System Access:
PJL: Enabled
PML: Enabled
NFS: Enabled
PostScript: Enabled
Secure Disk Erase Mode: Non-secure fast erase
Direct Ports (USB/IEEE 1284): Enabled

Paper Trays and Options

Default Paper Size: A4
Tray 1 Size: Any Size
Tray 2 Size: A4
Tray 3 Size: A4
Duplex Unit

Hardware Information

Product: LT V.92 1.0 MT5634SMI-V92 Data/Fax Modem
Modem Firmware Version: 2.36f
Modem Status: Operational / Enabled

Fax Information

Fax Job Count: 715

Fax Setup Settings

Location: None
Date Format: DD/MMM/YYYY
Current Date: 23-Feb-2014
Time Format: 24-hr
Current Time: 09:48
Phone Number: None
Company Name: None
Fax Dial Volume: Medium
Ringer Volume: Medium
Error Correction: Enabled
JBIG Compression: Enabled
Ring Interval: DEFAULT
Ring Frequency: DEFAULT
TCF T.30 Delay: DEFAULT
TCF Extend: DEFAULT

Fax Send Settings

Default Resolution: Standard (100x200dpi)
Fax Header: No
Dialing Mode: Tone
Redial on Busy: 3
Redial on No Answer: Never
Redial Interval: 5
Detect Dial Tone: Disabled
Dialing Prefix: Off
Dialing Prefix:
PC Fax Send: Enabled
Billing Code: Off
Billing Code Digits: 1

Fax Receive Settings

Rings to Answer: 2
Stamp Received Faxes: No
Fit to Page: Enabled
Paper Selection: 0
Fax Output Bin: 0
Forward Fax Number:
Fax Printing Schedule: On

Fax Report Setting

Fax Call Report: Print after any fax error
Thumbnail on Report: No
Fax T.30 Tracer Report: Never automatically print

 **Black Cartridge**
Order HP Part: Q5945A

25%

Maintenance Kit
Order HP Part: 110V-Q5998A, 220V-Q5999A

93%

Approximate Pages Remaining: 5419

(Will vary depending on types of documents printed.)

Low Reached: NO

Out Reached: NO

Serial Number: 11674109

Pages printed with this supply: 16257

Page Count by Paper Size:

Legal: 0

A4/Letter: 16242

A5/B5/Executive: 0

Custom/Other: 15

Number of Jobs Processed: 4445

First Install Date: 20080806

Last Used Date: 20140223

Document Feeder Kit
Order HP Part: Q5997A

99%

Ordering Information

Hewlett-Packard supplies can be ordered on the Internet, on-line through your device software, or by calling an authorized reseller. Refer to your User Guide for instructions.

Return & Recycling

Please return your genuine HP supplies for recycling to Hewlett-Packard. For more information, please visit us at <http://www.hp.com/go/recycle>

